



PREMIER SERIES

Perfect for Cleaning:

- ★ On-the-Road Cleaning
- ★ Schools
- ★ Rental Stores
- ★ Trucking
- ★ Warehouses
- ★ Hospitals
- ★ Chemical Processors





The Premier Series provides the highest level of quality & performance available in the industry today.



The Premier Series is compatible with all Streamliner trailers.

All major components are mounted for servicing convenience, with no panels to remove.



COIL SYSTEM

Our exclusive "Cool Touch Coil" actually forms the combustion chamber, eliminating troublesome insulation and outside hot spots. It also allows for better air flow which in turn provides better fuel combustion and efficiency.



ACCUMULATOR ASSEMBLY & UNLOADER ASSEMBLY

The All American Accumulator Assembly effectively manages high-pressure flow conditions that may ordinarily cause system failure. Heavy duty mounting of the pressure regulating valve eliminates fitting fatigue.



PUMP ASSEMBLY

Heavy-duty triplex plunger pump for years of dependable service.

MODEL #	GPM	PSI	HP	ENGINE	BURNER	COIL	BTU'S	FUEL CONSUMPTION	TEMPERATURE RISE	DIMENSION LxWxH	WEIGHT
PH5030VBOF	5	3000	16	VANGUARD GAS	OIL FIRED 12 VOLT	158", 1/2" SCHEDULE 80	315,000 BTU	2.25 GPH	115	48"x36"x40"	870 LBS
PH5030VGOD	5	3000	18	VANGUARD GAS	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	490,000 BTU	3.5 GPH	140	48"x36"x40"	870 LBS
PH5030KGOD	5	3000	18	KOHLER GAS	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	490,000 BTU	3.5 GPH	140	48"x36"x40"	870 LBS
PH5035KBOF	5	3500	18	KOHLER GAS	OIL FIRED 12 VOLT	158", 1/2" SCHEDULE 80	315,000 BTU	2.25 GPH	115	48"x36"x40"	870 LBS
PH5035HGOD	5	3500	20	HONDA GAS	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	490,000 BTU	3.5 GPH	140	48"x36"x40"	870 LBS
PH5035HBOF	5	3500	20	HONDA GAS	OIL FIRED 12 VOLT	158", 1/2" SCHEDULE 80	315,000 BTU	2.25 GPH	115	48"x36"x40"	870 LBS
PH8030HBOD	8	3000	24	HONDA GAS	OIL FIRED 115 VOLT	240", 1/2" SCHEDULE 80	560,000 BTU	4.0 GPH	140	48"x36"x40"	960 LBS
PH5050KBOD	5	5000	25	KOHLER GAS	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 160	560,000 BTU	4.0 GPH	140	48"x36"x40"	960 LBS
PH5035KGPD	5	3500	18	KOHLER GAS	PROPANE 12 VOLT	240", 1/2" SCHEDULE 80	490,000 BTU	LP-5.4 GPH	125	48"x36"x40"	870 LBS
PH5035PGPD	5	3500	18	KOHLER PROPANE	PROPANE 12 VOLT	240", 1/2" SCHEDULE 80	490,000 BTU	LP-5.4 GPH	125	48"x36"x40"	870 LBS
*PH5035DGOD	5.2	3500	26	KOHLER DIESEL	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	560,000 BTU	4.0 GPH	140	54"x54"x46"	1100 LBS
*PH7035DGOD	6.5	3500	26	KOHLER DIESEL	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	560,000 BTU	4.0 GPH	125	54"x54"x46"	1190 LBS
*PH8030DGOD	8	3000	26	KOHLER DIESEL	OIL FIRED 115 VOLT	158", 1/2" SCHEDULE 80	560,000 BTU	4.0 GPH	100	54"x54"x46"	1190 LBS

*Models have horizontal coils.

STANDARD FEATURES

- 1 1/4" Tubular steel frame construction
- Belt driven triplex plunger pump
- Stainless steel panels & coil wrap
- 3000 watt generator (115V only)
- Adjustable temperature control
- Electric start engine
- Dual 18 gallon non corrosive fuel tanks
- Trigger shut-off gun with wand
- Four quickchange spray nozzles
- 50 ft. high pressure hose with quick disconnects
- Stainless steel float tank
- Pulsation dampner for long life
- Racor Fuel Filter
- Adjustable high pressure detergent

OPTIONAL FEATURES

- Wheel Kit - 4 Pneumatic wheels W/ Handle
- Hour meter
- Wheel Kit - Swivel Hand Pull Cart
- Streamliner Trailer with 230, 330, 460, 535 gallon water tank
- Steam Combo
- UL1776 Listed

**7-5-1 YEAR
LIMITED
WARRANTY**



Contract Holder
Contract GS-07F-0302N

105 Broad Street, PO Box 288
Alcester, South Dakota, USA 57001
TEL: 800-541-7267 • FAX: 800-325-5682

www.allamericancleaningsystems.com

Bulletin #305-2010