

# HOT WATER PRESSURE WASHER

## DED SERIES DIESEL ENGINE DRIVE



### PERFECT FOR CLEANING

- Heavy Equipment
- Oil Rigs
- Tractor Trailers
- Railroad Locomotives
- Asphalt Equipment
- Concrete Equipment
- Logging Equipment
- Mining Equipment



### WHY CHOOSE ALKOTA

**There is no reason that machines need to be complicated to do their job.**

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the **USA**, so that you know you're getting an American-built machine.



10307K



10307KK,  
10307KKA



5357C



# DIESEL DRIVEN SERIES SPECIFICATION CHART

MODEL	3307F	5357C	5357	5357K	5407	5407K	5507
GPM	3.5	4.7	5	5	5	5	5
PSI	3000	3500	3500	3500	4000	4000	5000
Engine	Kohler KD430 Air Cooled, Electric Start	Kubota Z602 Water Cooled, Electric Start	Kohler KDW1003 Water Cooled, Electric Start	Kubota D902 Water Cooled, Electric Start	Kohler KDW1003 Water Cooled, Electric Start	Kubota D902 Water Cooled, Electric Start	Kohler KDW1003 Water Cooled, Electric Start
BTU	235,000	355,000	550,000	550,000	550,000	550,000	550,000
Burner Voltage	12V DC	12V DC	115V	115V	115V	115V	115V
Coil	95' 1/2" Sch.80	126' 1/2" Sch. 80	158' 1/2" Sch. 80	158' 1/2" Sch. 80	158' 1/2" Sch.80	158' 1/2" Sch.80	158' 1/2" Sch.160
Coil Size	14"	14"	18"	18"	18"	18"	18"
Fuel Tank	11 Gallon	11 Gallon	27 Gallon	30 Gallon	27 Gallon	30 Gallon	27 Gallon
Temperature	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F
Chemical	Low Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering
Pump	GP Triplex	GP Triplex	GP Triplex	GP Triplex	Comet Triplex	GP Triplex	GP Triplex
Dimension	46"L x 32"W x 43"H	48"L x 34"W x 38.5"H	54"L x 45"W x 46"H	60"L x 48"W x 47"H	54"L x 45"W x 46"H	60"L x 48"W x 47"H	54"L x 45"W x 46"H
Weight	560 lbs.	845 lbs.	1,260 lbs.	1,360 lbs.	1,260 lbs.	1,350 lbs.	1,260 lbs.

MODEL	5507K	8307	8307K	10307K	10307KK	10307KKA
GPM	5	8	8	10	10	10
PSI	5000	3000	3000	3000	3000	3000
Engine	Kubota D1305 Water Cooled, Electric Start	Kohler KDW1003 Water Cooled, Electric Start	Kubota D1305 Water Cooled, Electric Start	Kubota D1305 Water Cooled, Electric Start	Kubota D1305 Water Cooled, Electric Start	Kubota D1305 Water Cooled, Electric Start
BTU	550,000	550,000	690,000	785,000	785,000	710,000
Burner Voltage	115V	115V	115V	115V	115V	12V DC
Coil	158' 1/2" Sch.160	158' 1/2" Sch.80	243' 1/2" Sch.80	483' 3/4" Sch. 80	337' 3/4" Sch. 80	337' 3/4" Sch. 80
Coil Size	18"	18"	18"	30"	24"	24"
Fuel Tank	30 Gallon	27 Gallon	50 Gallon	50 Gallon	50 Gallon	50 Gallon
Temperature	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F	Up to 210 F
Chemical	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering
Pump	GP Triplex	GP Triplex	GP Triplex	GP Triplex	GP Triplex	GP Triplex
Dimension	60"L x 48"W x 47"H	54"L x 45"W x 46"H	60"L x 48"W x 47"H	72"L x 50"W x 65"H	64.5"L x 55.5"W x 61.5"H	64.5"L x 55.5"W x 61.5"H
Weight	1,260 lbs.	1,260 lbs.	1,400 lbs.	2,150 lbs.	1,560 lbs.	1,560 lbs.

## Standard Features

- Belt Drive Triplex Plunger Pump
- Adjustable Temperature Control
- Soft Dampening System for Long Life of Fittings, Pump & Coil
- 50 ft. hose, shut off gun and 42" wand
- Schedule 80 Hydro Insulated Coil
- Winterizing Valve for protection during cold weather
- Stainless Steel Float tank (Excluded 3307F)
- Heavy Tubular Steel Construction

## Available Options

- Nozzle Kit
- Steam Option
- Dual Gun System
- Stainless Steel Frame
- Hour Meter
- Downstream Soap
- Dual Gun Setup
- Wireless Remote
- Pump Clutch
- Pressure Gauge
- Temperature Gauge
- 12 burner in place of 115V generator.

## FOR BETTER CLEANING



Clean Better with **Alkota Biodegradable** detergents specially formulated for high pressure cleaning.

All pressure washer detergents are blended with sealant to reduce scale buildup in the heating oil, pump and fittings. This improves equipment performance and minimizes replacement and repair cost.

Distributed by:



**Alkota Cleaning Systems Inc.**  
Alcester, South Dakota 57001

**For more information call:**  
(800) 255-6823 / (605) 934-2222 or  
Fax: (800) 325-5682 / (605) 934-1808  
Web Access: [www.alkota.com](http://www.alkota.com)

## CERTIFICATIONS



© 2020 Alkota Cleaning Systems  
Specifications subject to change without notice  
Printed in U.S.A. / Form #: ALK-DDS-0420