

HOT WATER PRESSURE WASHER

GAS FIRED SERIES

NATURAL & LP GAS HOT WATER



APPLICATIONS

- Food Processing
- Truck Washing
- Manufacturing
- Industrial Repair
- Automotive Repair
- Railroad Maintenance
- In Plant Cleaning Systems



WHY CHOOSE ALKOTA

There is no reason that machines need to be complicated to do their job.

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an Alkota pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At Alkota we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the USA, so that you know you're getting an American-built machine.



MODEL	2161	3111	3201	3241	3301	4181	4201
GPM	2.1	3	3	3	3	4	3.6
PSI	1600	1100	2000	2400	3000	1800	2000
HP	2.3	2.3	4	5	6	5	5
Voltage	115V/ 1 PH/20 AMP	115V/ 1 PH/20 AMP	230 V/1 PH/20 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP	230 V/1 PH/30 AMP
BTU	235,000	320,000	320,000	320,000	320,000	320,000	320,000
Coil Size	14" Sch. 80	14" Sch. 80	14" Sch. 80	14" Sch. 80	14" Sch. 80	18" Sch. 80	14" Sch. 80
Gas Consumption	NG-191 CU.FT. PER HR. LP-2.2 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH	NG-305 CU.FT. PER HR. LP-3.5 GPH
Stack	10"	10"	10"	10"	10"	12"	10"
Weight	600	600	610	615	630	700	615
Dimensions	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H
MODEL	4231	4301	5181	5231	5301	5301	5401
GPM	4	4	5	5	5	5	5
PSI	2300	3000	1800	2300	3000	3000	4000
HP	6	8	6	8	10	10	15
Voltage	230 V/1 PH/30 AMP	230 V/1 PH/40 AMP	230 V/1 PH/30 AMP	230 V/1 PH/40 AMP	230 V/3 PH/30 AMP	230 V/1 PH/ 50 AMP	230 V/3 PH/40 AMP
BTU	320,000	320,000	440,000	440,000	440,000	440,000	440,000
Coil Size	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80	18" Sch. 80
Gas Consumption	NG-305 CU.FT. PER HR. LP-3.8 GPH	NG-305 CU.FT. PER HR. LP-3.8 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH
Stack	12"	12"	12"	12"	12"	12"	12"
Weight	800	810	800	825	860	880	885
Dimensions	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H
MODEL	7201	6231	5501	7301	8181	8251	8351
GPM	7	6	5	7	8	8	8
PSI	2000	2300	5000	3000	1800	2500	3500
HP	10	10	20	15	10	15	20
Voltage	230 V/3 PH/30 AMP	230 V/3 PH/30 AMP	230 V/3 PH/50 AMP	230 V/3 PH/40 AMP	230 V/3 PH/30 AMP	230 V/3 PH/40 AMP	230 V/3 PH/50 AMP
BTU	660, 000	660, 000	440,000	660, 000	660, 000	660, 000	660, 000
Coil Size	18" Sch. 80	18" Sch. 80	18" Sch. 160	24" Sch. 80	18" Sch. 80	24" Sch. 80	24" Sch. 80
Gas Consumption	NG-630 CU.FT. PER HR. LP-7.25 GPH	NG-630 CU.FT. PER HR. LP-7.25 GPH	NG-420 CU.FT. PER HR. LP-5.4 GPH	NG-630 CU.FT. PER HR. LP-7.25 GPH	NG-630 CU.FT. PER HR. LP-7.25 GPH	NG-630 CU.FT. PER HR. LP-7.25 GPH	NG-630 CU.FT. PER HR. LP-7.25 GPH
Stack	12"	12"	12"	12"	12"	12"	12"
Weight	860	860	960	1390	860	1385	1410
Dimensions	55" L x 26" W x 57" H	55" L x 26" W x 57" H	55" L x 26" W x 57" H	69" L x 31" W x 65" H	55" L x 26" W x 57" H	69" L x 31" W x 65" H	69" L x 31" W x 65" H
MODEL	10201	10301					
GPM	10	10					
PSI	2000	3000					
HP	15	20					
Voltage	230 V/3 PH/40 AMP	230 V/3 PH/50 AMP					
BTU	880,000	880,000					
Coil Size	30" Sch. 80	30" Sch. 80					
Gas Consumption	NG-840 CU.FT. PER HR. LP-9.7 GPH	NG-840 CU.FT. PER HR. LP-9.7 GPH					
Stack	12"	12"					
Weight	1640	1710					
Dimensions	69" L x 31" W x 65" H	69" L x 31" W x 65" H					

Standard Features

- Natural Gas or LP
- Belt-Drive triplex plunger pump
- Soft dampening system for long life of high pressure fittings, pump & coil
- 50 ft. hose, shut off gun and wand
- Schedule 80 Hydro Insulated Coil
- Stainless Steel Float Tank
- Electronic Ignition
- Draft Diverter
- Smart Timer - Auto start/ stop with 20 sec. delay

Available Options

- Four Nozzle kit
- Steam Option
- Remote
- Soap Solenoid for Remote
- SS Coil Wrapper
- Digital Temperature Control
- 460V, 3 Phase
- Stainless Steel Frame
- Stainless Steel Coil
- Oil Fired Burner
- Hour Meter

Distributed by:



Alkota Cleaning Systems Inc.

Alcester, South Dakota 57001

For more information call:

(800) 255-6823 / (605) 934-2222 or

Fax: (800) 325-5682 / (605) 934-1808

Web Access: www.alkota.com

CERTIFICATIONS



© 2021 Alkota Cleaning Systems

Specifications subject to change without notice

Printed in U.S.A. / Form #: ALK-GFS-0320