HOT WATER PRESSURE WASHER X4 GAS/ DIESEL ENGINE SERIES

PORTABLE GASOLINE ENGINE BELT DRIVE

PERFECT FOR CLEANING

- Trucking
- Construction
- Parks
- Schools
- Shopping Centers
- Side Walks
- Farms





There is no reason that machines need to be complicated to do their job.

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the **USA**, so that you know you're getting an American-built machine.



GAS ENGINE DRIVE SPECIFICATION CHART

MODEL 3255X4V		3305X4	3307X4	4405X4	5355XV4	
GPM	3.0 GPM	3.0 GPM	3.5 GPM	4.0 GPM	4.8 GPM	
PSI	2500 PSI	3000 PSI	3000 PSI	4000 PSI	3500 PSI	
BTU	170, 000 BTU 12V	275, 000 BTU 12V	275, 000 BTU 12V	355, 000 BTU 12V	355, 000 BTU 12V	
Engine	e 6 1/2 HP, Vanguard, Recoil Start GX270, Honda, Recoil St		KD440, Kohler, Diesel, Electric Start	GX390 Vanguard, Recoil Start	Vanguard 18 HP (Electric Start)	
Pump	GP	GP	AR	GP	GP	
Chemical	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	High Pressure Metering	
Coil	95' 1/2" ID Sch. 80	126' 1/2" ID Sch. 80	126' 1/2" ID Sch. 80	126' 1/2" ID Sch. 80	126' 1/2" ID Sch. 80	
Fuel Consumption	1.2 GPH	1.95 GPH	1.95 GPH	1.95 GPH	1.95 GPH	
Fuel Tank Capacity	Burner - 8 gal. Gas - 1 gal.	Burner - 8 gal. Gas - 1.46 gal.	Burner - 8 gal. Diesel - 1.3 Engine	Burner - 8 gal. Gas - 1.7 gal.	Burner - 8 gal. Gas - 1.75 gal.	
Temp Rise	Up to 210° F	Up to 210° F	Up to 210° F	Up to 210° F	Up to 210° F	
Weight	550 lbs.	650 lbs.	650 lbs.	650 lbs.	690 lbs.	
Dimensions	48" L x 34" W x 38 1/2" H	53" L x 31.5" W x 50" H	53" L x 31.5" W x 50" H	53" L x 31.5" W x 50" H	53" L x 31.5" W x 50" H	

Standard Features

- · Burns Kerosene, Diesel or Home Heating Oil
- · Belt drive triplex ceramic plunger pump
- Soft Dampening system for long life of high pressure fittings, pump & coil
- Adjustable Front axle for proper weight distribution
- · Corrosion resistant float tank
- Winterizing valve for protection during cold weather
- Built in Wand Holder
- 50 ft. hose, shut off gun and 42" insulated wand
- Four pneumatic wheels
- · Schedule 80 Hydro Insulated Coil
- High Pressure Detergent

Available Options

- Nozzle Kit
- Hour Meter
- Flat Free Wheels
- Steam Option
- Adjustable Temperature Control
- Stainless Steel Frame

FOR BETTER CLEANING



Clean Better with Alkota Biodegradable detergents specially formulated for high pressure cleaning.

All pressure washer detergents are blended

with sealted to reduce scale buildup in the heating oil, pump and fittings. This improves equipment performance and minimizes replacement and repair cost.



Alkota Cleaning Systems Inc. Alcester, South Dakota 57001

Aicester, South Dakota 5700

For more information call: (800) 255-6823 / (605) 934-2222 or Fax: (800) 325-5682 / (605) 934-1808 Web Access: www.alkota.com

CERTIFICATIONS





© 2020 Alkota Cleaning Systems Specifications subject to change without notice Printed in U.S.A. / Form #: ALK-GES-0420

_							
L)	IIS.	trı	hı	ute	d	h١	/٠